

Drill Hole	Including	Zone	From (m)	To (m)	Sample Length (m)	Grade (g/t Au)	Azimuth	Dip	Northing	Easting	Elevation	Depth
TL21-529B		HW	460.00	465.00	5.00	1.06	346	-74	5511597	528353	389	750
TL21-529B		Main	640.55	646.00	5.45	0.89						
TL21-529B		C	706.84	709.30	2.46	0.81						
TL21-530		HW	99.00	100.07	1.07	6.78	355	-77	5511905	528475	393	522
TL21-530		HW	105.00	111.00	6.00	0.64						
TL21-530		HW	120.00	121.00	1.00	3.33						
TL21-530		Main	346.34	348.34	2.00	0.90						
TL21-530		C	462.00	470.00	8.00	0.39						
TL21-530		C	506.95	511.00	4.05	0.87						
TL21-531B		HW	184.00	188.40	4.40	2.25	345	-76	5511790	528341	390	582
	<i>including</i>		186.00	187.00	1.00	8.60						
TL21-531B		HW	200.00	211.00	11.00	0.47						
TL21-531B		HW	243.00	245.00	2.00	1.42						
TL21-531B		Main	443.00	445.00	2.00	0.80						
TL21-531B		C	558.60	560.80	2.20	0.61						
TL21-532		HW	543.00	551.60	8.60	0.29	345	-77	5511563	528295	389	846
TL21-532		HW	568.00	570.85	2.85	2.57						
	<i>including</i>		569.00	570.00	1.00	5.82						
TL21-532		C	828.00	834.00	6.00	1.27						
	<i>including</i>		828.00	829.00	1.00	4.53						
	<i>and including</i>		833.00	834.00	1.00	2.26						
TL21-533B		HW	528.75	538.15	9.40	0.96	352	-76	5511563	528295	389	810
	<i>including</i>		530.65	532.50	1.85	2.57						
TL21-533B		HW	563.00	567.00	4.00	2.47						
	<i>including</i>		563.00	564.00	1.00	8.49						
TL21-533B		Main	768.00	770.00	2.00	0.99						
TL21-534		Main	244.00	252.00	8.00	2.10	358	-68	5511910	528345	390	387
	<i>including</i>		245.00	246.00	1.00	3.81						
	<i>and including</i>		251.00	252.00	1.00	7.77						
TL21-534		C	347.50	351.50	4.00	0.65						
TL21-534		C	380.90	384.20	3.30	0.65						
TL21-535		Main	508.85	522.00	13.15	0.42	345	-75	5528147	547910	413	624
	<i>including</i>		516.90	517.45	0.55	3.59						
TL21-535		C	588.02	591.15	3.13	0.87						
TL21-536		Main	639.90	653.95	14.05	2.31	342	-74	5511560	528112	391	708
	<i>including</i>		646.50	652.30	5.80	4.93						
	<i>including</i>		651.50	652.30	0.80	31.40						
TL21-537A		HW	470.00	474.65	4.65	0.53	344	-75	5511648	528063	394	648
TL21-537A		Main	560.27	565.45	5.18	1.13						
	<i>including</i>		563.14	563.67	0.53	7.60						
TL21-538		West - HW	54.00	60.00	6.00	1.07	357	-50	5511725	527200	399	252
	<i>including</i>		54.00	55.50	1.50	2.41						

Notes

Reported intervals are drilled core lengths and do not indicate true widths

All grades uncut, no capping.

Drill Hole	Including	Zone	From (m)	To (m)	Sample Length (m)	Grade (g/t Au)	Azimuth	Dip	Northing	Easting	Elevation	Depth
TL21-538		West - HW	72.00	77.00	5.00	1.50						
	<i>including</i>		72.00	73.00	1.00	5.22						
TL21-538		West - Main	122.00	132.00	10.00	0.49						
TL21-538		West - Main FW	140.00	146.10	6.10	0.49						
TL21-538		West - C	221.00	221.90	0.90	5.97						
TL21-539		West - HW	46.10	63.35	17.25	0.30	357	-50	5511725	527150	399	276
TL21-539		West - Main	122.05	146.50	24.45	0.75						
	<i>including</i>		135.00	146.50	11.50	1.28						
	<i>including</i>		135.00	136.00	1.00	6.01						
	<i>and including</i>		144.00	145.50	1.50	2.30						
TL21-539		West - C	216.40	218.50	2.10	2.56						
	<i>including</i>		217.45	218.50	1.05	3.74						
TL21-540		HW	1.50	19.40	17.90	0.32	358	-54	5511750	527075	397	252
	<i>including</i>		1.50	7.00	5.50	0.59						
	<i>including</i>		6.00	7.00	1.00	1.54						
TL21-540		Main	83.50	84.00	0.50	4.12						
TL21-540		Main	94.00	111.50	17.50	0.98						
	<i>including</i>		100.00	107.00	7.00	2.02						
	<i>including</i>		101.20	102.00	0.80	7.74						
	<i>and including</i>		106.00	107.00	1.00	3.61						
TL21-540		C	173.00	196.00	23.00	0.46						
	<i>including</i>		187.00	188.00	1.00	6.00						
TL21-541		HW	406.90	411.60	4.70	0.52	335	-76	5511660	528333	389	729
TL21-541		HW	459.60	461.90	2.30	0.89						
TL21-541		Main	643.00	660.90	17.90	0.46						
	<i>including</i>		647.20	656.00	8.80	0.73						
	<i>and including</i>		651.00	653.00	2.00	1.67						
TL21-542		HW	3.90	17.30	13.40	0.44	359	-55	5511750	527040	397	252
	<i>including</i>		5.00	6.00	1.00	1.66						
TL21-542		Main	90.00	118.00	28.00	0.40						
	<i>including</i>		94.00	95.00	1.00	2.00						
	<i>and including</i>		96.00	97.00	1.00	1.35						
TL21-542		C	157.50	161.00	3.50	0.69						
TL21-543		Main	35.70	44.00	8.30	0.59	358	-50	5511790	527025	395	201
TL21-543		Main	55.00	58.50	3.50	0.47						
TL21-543		C	126.10	127.40	1.30	19.80						
	<i>including</i>		126.10	126.80	0.70	33.90						
TL21-544		West - HW	54.50	58.60	4.10	0.54	357	-55	5511735	526930	395	222
TL21-544		West - Main	118.00	132.00	14.00	0.34						
TL21-545		Main	483.40	502.00	18.60	0.54	350	-70	5511600	527970	389	558
	<i>including</i>		489.00	497.40	8.40	0.96						
	<i>and including</i>		493.00	493.30	0.30	10.90						

Notes

Reported intervals are drilled core lengths and do not indicate true widths
All grades uncut, no capping.

Drill Hole	Including	Zone	From (m)	To (m)	Sample Length (m)	Grade (g/t Au)	Azimuth	Dip	Northing	Easting	Elevation	Depth
TL21-547		Main	669.00	697.50	28.50	0.60	350	-80	5511600	527970	389	741
	<i>including</i>		669.00	674.20	5.20	1.83						
	<i>and including</i>		669.00	670.00	1.00	6.95						
TL21-548B		HW	436.60	438.10	1.50	2.14	323	-75	5511660	528333	389	738
TL21-548B		HW	530.60	532.10	1.50	1.97						
TL21-548B		Main	634.50	657.00	22.50	0.69						
	<i>including</i>		634.50	640.50	6.00	1.47						
	<i>including</i>		634.50	636.00	1.50	4.22						
	<i>and including</i>		645.00	651.00	6.00	0.90						
TL21-549		HW	546.00	551.40	5.40	0.93	350	-78	5511600	527970	389	684
	<i>including</i>		546.00	547.10	1.10	3.88						
TL21-549		HW	578.00	579.10	1.10	5.75						
TL21-549		Main	612.20	621.00	8.80	1.56						
	<i>including</i>		612.20	613.00	0.80	12.10						
TL21-550		HW	422.50	426.00	3.50	1.61	350	-74	5511655	528050	390	612
	<i>including</i>		422.50	424.00	1.50	3.26						
TL21-550		Main	482.00	495.40	13.40	0.48						
TL21-550		Main	508.87	514.00	5.13	0.89						
TL21-550		C	573.50	576.50	3.00	1.50						
	<i>including</i>		573.50	575.00	1.50	2.42						
TL21-551		HW	11.30	13.30	2.00	1.03	357	-50	5511780	526915	394	195
		Main	65.00	69.00	4.00	0.77						
TL21-552		West - HW	5.30	10.46	5.16	0.59	354	-52	5511747	526979	396	240
TL21-552		C	146.00	148.00	2.00	1.99						
	<i>including</i>		146.00	147.00	1.00	3.59						
TL21-553		HW	642.00	643.50	1.50	2.16	335	-79	5511625	528290	389	855
TL21-553		Main	711.30	723.10	11.80	1.51						
	<i>including</i>		711.30	712.30	1.00	6.87						
	<i>including</i>		720.10	723.10	3.00	3.02						
	<i>and including</i>		722.10	723.10	1.00	6.13						
TL21-553		C	796.30	803.50	7.20	1.01						
	<i>including</i>		798.50	799.60	1.10	3.56						
TL21-554		West - Main	98.00	107.50	9.50	0.37	357	-55	5511735	526840	395	255
TL21-554		West - C	121.50	129.10	7.60	0.54						
	<i>including</i>		128.00	129.10	1.10	2.86						
TL21-555		West - Main	64.00	70.30	6.30	0.49	357	-55	5511715	526675	395	204
TL21-555		West - C	133.50	135.00	1.50	1.50						
TL21-555		West - C	144.00	157.00	13.00	0.46						
	<i>and including</i>		153.00	157.00	4.00	0.66						
TL21-556		West - HW	71.00	74.00	3.00	1.05	357	-55	5511700	526570	395	201
	<i>including</i>		72.50	74.00	1.50	1.67						
TL21-556		West - Main	118.00	134.00	16.00	0.42						

Notes

Reported intervals are drilled core lengths and do not indicate true widths
All grades uncut, no capping.

Drill Hole	Including	Zone	From (m)	To (m)	Sample Length (m)	Grade (g/t Au)	Azimuth	Dip	Northing	Easting	Elevation	Depth
	<i>including</i>		118.00	119.50	1.50	1.36						
	<i>and including</i>		132.50	134.00	1.50	1.52						
TL21-557		West - HW	156.50	161.50	5.00	0.45	357	-55	5511600	526585	395	312
TL21-557		West - Main	187.50	198.00	10.50	0.66						
TL21-557		West - C	245.00	248.00	3.00	0.54						
TL21-557		West - C	270.60	274.50	3.90	0.45						
TL21-559		West - Main	162.00	176.00	14.00	4.00	357	-55	5511630	526610	395	261
	<i>including</i>		162.00	167.50	5.50	9.55						
	<i>including</i>		164.50	166.00	1.50	24.40						
	<i>and including</i>		166.00	167.50	1.50	8.60						
TL21-559		West - C	212.00	237.70	25.70	0.57						
	<i>including</i>		237.00	237.70	0.70	7.80						
TL21-560		Main	198.80	200.00	1.20	1.29	357	-55	5511660	526525	395	225
TL21-561		HW	169.50	177.00	7.50	0.34	347	-69	5511775	528275	390	441
TL21-561		HW	320.00	324.60	4.60	0.63						
TL21-561		Main	375.00	390.00	15.00	52.60						
	<i>including</i>		375.00	383.60	8.60	1.37						
	<i>and including</i>		383.60	384.44	0.84	870.00						
	<i>and including</i>		384.44	385.18	0.74	25.80						
	<i>and including</i>		385.18	385.68	0.50	47.50						
TL21-562		West - Main	156.00	161.00	5.00	0.75	357	-55	5511650	526750	395	282
	<i>including</i>		160.00	161.00	1.00	2.92						
TL21-562		West - Main	196.00	200.50	4.50	0.51						
TL21-562		West - C	223.00	230.50	7.50	0.46						
	<i>including</i>		227.50	230.50	3.00	0.77						
TL21-563C		HW	313.00	316.00	3.00	1.22	348	-79	5511653	528040	387	615
	<i>including</i>		313.00	314.50	1.50	1.77						
TL21-563C		Main	559.00	568.60	9.60	0.60						
	<i>including</i>		559.00	560.00	1.00	2.99						
TL21-564		West - Main	87.50	99.50	12.00	0.44	357	-55	5511720	526740	395	252
	<i>including</i>		98.00	99.50	1.50	1.50						
TL21-564		West - C	108.50	120.00	11.50	0.39						
TL21-565		HW	5.60	9.00	3.40	0.85	357	-55	5511720	526790	395	201
TL21-565		HW	51.50	52.80	1.30	7.12						
TL21-565		Main	125.20	128.00	2.80	0.82						
TL21-565		C	167.00	168.50	1.50	1.99						
TL21-566		West - Main	169.50	177.00	7.50	0.36	357	-55	5511650	526795	395	327
TL21-566		West - C	194.90	207.50	12.60	1.08						
	<i>including</i>		194.90	197.50	2.60	1.70						
	<i>and including</i>		206.00	207.50	1.50	4.94						
TL21-574		Main	633.00	637.50	4.50	0.53	348	-79	5511598	527966	387	675

Notes

Reported intervals are drilled core lengths and do not indicate true widths
All grades uncut, no capping.