

<b>Drill Hole</b>	<b>X_UTM</b>	<b>Y_UTM</b>	<b>Z_Elev</b>	<b>Az</b>	<b>Dip</b>	<b>Depth (m)</b>
TL43W1	527674.10	5511623.22	392.21	360	-75	458.00
TL43W2	527674.10	5511623.22	392.21	360	-75	457.90
TL43W3	527674.10	5511623.22	392.21	360	-75	459.00
TL44W1	527818.81	5511627.00	392.29	360	-82	571.10
TL44W2	527818.81	5511627.00	392.29	360	-82	568.90
TL44W3	527818.81	5511627.00	392.29	360	-82	572.00
TL88W	527947.66	5511730.94	399.21	360	-65	192.00
TL96W	527891.81	5511654.00	396.04	360	-68	405.00
TL125W1	528070.14	5511638.01	392.70	360	-68	437.00
TL125W2	528070.14	5511638.01	392.70	360	-68	437.00
TL126W1	528272.64	5511737.26	391.63	360	-80	500.00
TL126W2	528272.64	5511737.26	391.63	360	-80	503.00
TL126W3	528272.64	5511737.26	391.63	360	-80	503.00
TL127W1	528477.55	5511900.12	393.99	360	-80	521.00
TL127W2	528477.55	5511900.12	393.99	360	-80	521.00
TL127W3	528477.55	5511900.12	393.99	360	-80	521.00
TL128W1	527476.01	5511639.35	394.66	360	-81	421.70
TL128W2	527476.01	5511639.35	394.66	360	-81	425.00
TL128W3	527476.01	5511639.35	394.66	360	-81	422.00
TL129W1	527276.10	5511628.15	395.94	360	-87	479.00
TL129W2	527276.10	5511628.15	395.94	360	-87	479.00
TL129W3	527276.10	5511628.15	395.94	360	-87	479.00
TL133W1	527990.81	5511630.00	397.38	360	-85	649.90
TL133W2	527990.81	5511630.00	397.38	360	-85	649.60
TL133W3	527990.81	5511630.00	397.38	360	-85	653.00
TL136W1	528679.81	5511925.00	392.00	360	-83	590.00
TL136W2	528679.81	5511925.00	392.00	360	-83	590.00
TL137W1	527739.81	5511632.00	389.67	360	-90	755.00
TL137W2	527739.81	5511632.00	389.67	360	-90	755.00
TL170W1	528069.93	5511655.34	393.27	360	-68	460.00